

## DCE-L 6 T

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 206500

### The main features

Compact instantaneous water heater with electronic open-loop control

Compact dimensions for unobtrusive integration in the living space

Easy to use backlit multifunction display

Safe use due to adjustable electronic temperature limit as anti-scalding protection

Sufficient hot water for multiple draw-off points



DCE-L 8 T

Product-No.: 206499



Type	DCE-L 6 T	DCE-L 8 T
Part no.	206500	206499

## Technical data

Height	372 mm	372 mm
Width	217 mm	217 mm
Depth	109 mm	109 mm
Weight	2.5 kg	2.5 kg
Electrical fuse protection	AutoShield	AutoShield
Rated output	6,0-7,2 kW	8,0-9,6 kW
Electrical connection	1/N/PE~220-240 V	1/N/PE~220-240 V
Rated current	27,3-30,0 A	36,4-40,0 A
Heating element	Direct Coil# bare wire	Direct Coil# bare wire
Type	Closed outlet	Closed outlet
Automatic flow switch	true	true
Cylinder type	Plastic	Plastic
Temperature setting	Variable 30-60 °C	Variable 30-60 °C
Temperature control	Electronic temperature control	Electronic temperature control
Temperature memory buttons	2	2
IP rating	IP25	IP25

Colour	white	white
Water connection	1/2 inch	1/2 inch
Starting flow rate	1.3 l/min	1.3 l/min

## **Contact information**

You have questions? We appreciate to help you:

Call 02-021-9300

Write an email to [th-info@stiebel-eltron.com](mailto:th-info@stiebel-eltron.com)

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.