PRODUCT-NO.: 233226



# DHC 6 XG (STE)

**COMPACT INSTANTANEOUS WATER HEATER** 

A slimline design with a depth of just 7.3 cm if space under your sink or washbasin is limited, along with the highly durable copper tank. The multi-point unit is suitable for bathrooms with several draw-off points, e.g. washbasin, bath and shower.

Choose from various colours: a white casing for the 4000 watt version or silver casing for the 6000 and 8000 watt models.



#### The main features

Temperature adjustment via stepless power control

Sufficient hot water for multiple draw-off points

Corrosion-resistant copper heating element and tank

Extra slimline design with a depth of just 7.3 cm

Anti-scalding and overheating protection with thermal cut-out

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

Protection class IP25 (splash-proof)



DHC 4 XG (STE)

Product-No.: 235024



DHC 8 XG (STE)

Product-No.: 233227









| Туре     | DHC 4 XG (STE) | DHC 6 XG (STE) | DHC 8 XG (STE) |
|----------|----------------|----------------|----------------|
| Part no. | 235024         | 233226         | 233227         |

## Technical data

| Height                     | 342 mm                       | 342 mm                       | 342 mm                       |
|----------------------------|------------------------------|------------------------------|------------------------------|
| Width                      | 216 mm                       | 216 mm                       | 216 mm                       |
| Depth                      | 73 mm                        | 73 mm                        | 73 mm                        |
| Weight                     | 2 kg                         | 2 kg                         | 2.2 kg                       |
| Electrical fuse protection | ELCB                         | ELCB                         | ELCB                         |
| Rated output               | 4.0 kW                       | 6.0 kW                       | 8.0 kW                       |
| Rated current              | 18.2 A                       | 27.3 A                       | 36.4 A                       |
| Water connection           | 1/2 inch                     | 1/2 inch                     | 1/2 inch                     |
| Shutdown value             | 1.4 I/min                    | 2.1 l/min                    | 2.7 I/min                    |
| Starting flow rate         | 1.8 I/min                    | 2.5 l/min                    | 3.1 I/min                    |
| Туре                       | Closed outlet                | Closed outlet                | Closed outlet                |
| Automatic flow switch      | true                         | true                         | true                         |
| Cylinder type              | Copper                       | Copper                       | Copper                       |
| Temperature setting        | Stepless                     | Stepless                     | Stepless                     |
| Temperature control        | Output control               | Output control               | Output control               |
| Anti-scalding protection   | Thermostat with manual reset | Thermostat with manual reset | Thermostat with manual reset |
| IP rating                  | IP25                         | IP25                         | IP25                         |



Colour white silver silver



## **Contact information**

You have questions? We appreciate to help you: Call 02-021-9300 Write an email to th-info@stiebel-eltron.com

## Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.