DE 45 E (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

The main features

Temperature adjustment via stepless power control

Non-slip power selector

Complete set optimised for a single shower

Highly efficient composite polymer tank for reduced heat loss and electricity consumption

Corrosion-free copper heating element for longer service life

5-in-1 shower head with wall mounting bracket

Anti-scalding and overheating protection with double action thermostat

Protection class IP25 (splash-proof)

Quick and easy installation

Automatic on/off control with flow switch

Flame-retardant electronic circuit board for extra safety

Suitable for operation with low water pressure

Power "ON" shown by LED light on the appliance cover



DE 35 E (STE) Product-No.: 203183

PRODUCT-NO.: 203184



Туре	DE 35 E (STE)	DE 45 E (STE)
Part no.	203183	203184

Technical data

Cold water connection1/2 inch1/2 inchElectrical tuse protectionELSDELSDRated output3,500 W4,500 WElectrical connection1/N/PE-220-240 VRated voltage220-240 VRated current15.9 A21-24 ADisplaywithoutWithoutHaating elementCopper tubularCopper tubularTypeOpen outletOpen outletHeating materialPlasticPlasticTemperature settingVariableVariableTemperature controlOutput controlOutput controlAnti-scalding protectionS-in-1 shower head with wall mounting bracketS-in-1 shower head with wall mounting bracket			
Rated output3,500 W4,500 WElectrical connection1/N/PE-220-240 VRated voltage220-240 VRated current15.9 A21-24 ADisplaywithoutwithoutHeating elementCopper tubularTypeOpen outletOpen outletAutomatic flow switchtruetrueHeating materialPlasticTemperature settingVariableAnti-scalding protectionDouble acting thermostatShower accessories5-in-1 shower head with wall	Cold water connection	1/2 inch	1/2 inch
Electrical connection 1/N/PE-220-240 V Rated voltage 220-240 V Rated current 15.9 A 21-24 A Display without without Heating element Copper tubular Copper tubular Type Open outlet Open outlet Heating material Plastic Plastic Temperature control Output control Output control Anti-scalding protection Double acting thermostat Shower accessories Shower accessories Si-in-1 shower head with wall Shower accessories Si-in-1 shower head with wall	Electrical fuse protection	ELSD	ELSD
Rated voltage220-240 VRated current15.9 A21-24 ADisplaywithoutwithoutHeating elementCopper tubularCopper tubularTypeOpen outletOpen outletAutomatic flow switchtruetrueHeating materialPlasticPlasticTemperature settingOutput controlOutput controlAnti-scalding protectionDouble acting thermostatDouble acting thermostatShower accessoriesS-in-1 shower head with wallSince acting thermostat	Rated output	3,500 W	4,500 W
Rated current15.9 A21-24 ADisplaywithoutwithoutHeating elementCopper tubularCopper tubularTypeOpen outletOpen outletAutomatic flow switchtruetrueHeating materialPlasticPlasticTemperature settingVariableVariableAnti-scalding protectionDouble acting thermostatDouble acting thermostatShower accessories5-in-1 shower head with wall5-in-1 shower head with wall	Electrical connection		1/N/PE~220-240 V
DisplaywithoutwithoutHeating elementCopper tubularCopper tubularTypeOpen outletOpen outletAutomatic flow switchtruetrueHeating materialPlasticPlasticTemperature settingVariableVariableTemperature controlOutput controlOutput controlAnti-scalding protectionDouble acting thermostatDouble acting thermostatShower accessoriesS-in-1 shower head with wallS-in-1 shower head with wall	Rated voltage		220-240 V
Heating elementCopper tubularCopper tubularTypeOpen outletOpen outletAutomatic flow switchtruetrueHeating materialPlasticPlasticTemperature settingVariableVariableTemperature controlOutput controlOutput controlAnti-scalding protectionDouble acting thermostatDouble acting thermostatShower accessories5-in-1 shower head with wall5-in-1 shower head with wall	Rated current	15.9 A	21-24 A
TypeOpen outletOpen outletAutomatic flow switchtruetrueHeating materialPlasticPlasticTemperature settingVariableVariableTemperature controlOutput controlOutput controlAnti-scalding protectionDouble acting thermostatDouble acting thermostatShower accessories5-in-1 shower head with wall5-in-1 shower head with wall	Display	without	without
Automatic flow switchtruetrueHeating materialPlasticPlasticTemperature settingVariableVariableTemperature controlOutput controlOutput controlAnti-scalding protectionDouble acting thermostatDouble acting thermostatShower accessories5-in-1 shower head with wall5-in-1 shower head with wall	Heating element	Copper tubular	Copper tubular
Heating materialPlasticPlasticTemperature settingVariableVariableTemperature controlOutput controlOutput controlAnti-scalding protectionDouble acting thermostatDouble acting thermostatShower accessories5-in-1 shower head with wall5-in-1 shower head with wall	Туре	Open outlet	Open outlet
Temperature setting Variable Variable Temperature control Output control Output control Anti-scalding protection Double acting thermostat Double acting thermostat Shower accessories 5-in-1 shower head with wall 5-in-1 shower head with wall	Automatic flow switch	true	true
Temperature control Output control Output control Anti-scalding protection Double acting thermostat Double acting thermostat Shower accessories 5-in-1 shower head with wall 5-in-1 shower head with wall	Heating material	Plastic	Plastic
Anti-scalding protection Double acting thermostat Double acting thermostat Shower accessories 5-in-1 shower head with wall 5-in-1 shower head with wall	Temperature setting	Variable	Variable
thermostat thermostat thermostat Shower accessories 5-in-1 shower head with wall head with wall	Temperature control	Output control	Output control
Shower accessories 5-in-1 shower head with wall head with wall	Anti-scalding protection	-	-
head with wall head with wall		thermostat	thermostat
	Shower accessories	5-in-1 shower	5-in-1 shower
mounting bracket mounting bracket		head with wall	head with wall
		mounting bracket	mounting bracket

Colour	white	white
IP rating	IP25	IP25
Shutdown value	0.8 l/min	0.8 l/min
Starting flow rate	1.3 l/min	1.3 l/min
Depth	78 mm	78 mm
Height	308 mm	308 mm
Width	184 mm	184 mm
Weight	1 kg	1 kg

Contact information

You have questions? We appreciate to help you: Call 02-021-9300 Write an email to th-info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.