

WL 35 EC (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 235184

Experience an innovation of touch control with water kept precisely at the chosen temperature at all times.

All functions at a glance – the large LCD display gives you full control over the water temperature and special functions. Your favourite showering temperature is just a touch away via the 2 individually programmable memory buttons.

Start your day refreshed and enjoy alternating streams of hot and cold water to boost your circulation with Spa mode. Save electricity with ECO mode. Parents can rest easy as the child safety function allows you to set an upper temperature limit.



WL 45 EC (STE)

Product-No.: 235185

The main features

Maximum shower comfort with precise electronic output temperature control

User-friendly temperature adjustment via touch buttons

LCD display shows the shower water temperature at a glance

2 individually programmable temperature memory buttons

Complete set optimised for a single shower

Corrosion-resistant copper heating element and tank

5-in-1 shower head with slide bar for convenient height adjustment

ECO function for automatic control of the required power to save electricity

Spa function for hot/cold hydrotherapy to improve circulation

Child safety function limits the temperature to 35 °C

Anti-scalding and overheating protection with double action thermostat

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

Protection class IP25 (splash-proof)



| Type | WL 35 EC (STE) | WL 45 EC (STE) |
|----------|----------------|----------------|
| Part no. | 235184 | 235185 |

Technical data

| | | |
|----------------------------|---|---|
| Special functions | ECO mode; childproofing; SPA mode | ECO mode; childproofing; SPA mode |
| Heating element | Copper tubular | Copper tubular |
| Type | Open outlet | Open outlet |
| Automatic flow switch | true | true |
| Heating material | Copper | Copper |
| Temperature setting | Variable 30-42 °C via Touch Control | Variable 30-42 °C via Touch Control |
| Temperature control | Electronic temperature control | Electronic temperature control |
| Temperature memory buttons | 2 | 2 |
| Anti-scalding protection | Double acting thermostat | Double acting thermostat |
| Shower accessories | 5-in-1 shower head with slide bar | 5-in-1 shower head with slide bar |
| Colour | silver | silver |
| IP rating | IP25 | IP25 |
| Cold water connection | 1/2 inch | 1/2 inch |
| Electrical fuse protection | ELCB | ELCB |

| | | |
|-----------------------|------------------|------------------|
| Rated output | 3,500 W | 4,500 W |
| Electrical connection | 1/N/PE~220-240 V | 1/N/PE~220-240 V |
| Rated voltage | 220-240 V | 220-240 V |
| Rated current | 15.9 A | 20.5 A |
| Display | Standard | Standard |
| Shutdown value | 0.8 l/min | 0.8 l/min |
| Starting flow rate | 1.3 l/min | 1.3 l/min |
| Depth | 79 mm | 79 mm |
| Height | 326 mm | 326 mm |
| Width | 200 mm | 200 mm |
| Weight | 1.4 kg | 1.4 kg |

Contact information

You have questions? We appreciate to help you:

Call 02-021-9300

Write an email to th-info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.