

## WL 35 EC (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 235184

Experience an innovation of touch control with water kept precisely at the chosen temperature at all times.

All functions at a glance – the large LCD display gives you full control over the water temperature and special functions. Your favourite showering temperature is just a touch away via the 2 individually programmable memory buttons.

Start your day refreshed and enjoy alternating streams of hot and cold water to boost your circulation with Spa mode. Save electricity with ECO mode. Parents can rest easy as the child safety function allows you to set an upper temperature limit.



WL 45 EC (STE)

Product-No.: 235185

### The main features

Maximum shower comfort with precise electronic output temperature control

---

User-friendly temperature adjustment via touch buttons

---

LCD display shows the shower water temperature at a glance

---

2 individually programmable temperature memory buttons

---

Complete set optimised for a single shower

---

Corrosion-resistant copper heating element and tank

---

5-in-1 shower head with slide bar for convenient height adjustment

---

ECO function for automatic control of the required power to save electricity

---

Spa function for hot/cold hydrotherapy to improve circulation

---

Child safety function limits the temperature to 35 °C

---

Anti-scalding and overheating protection with double action thermostat

---

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

---

Protection class IP25 (splash-proof)



Type	WL 35 EC (STE)	WL 45 EC (STE)
Part no.	235184	235185

## Technical data

Special functions	ECO mode; childproofing; SPA mode	ECO mode; childproofing; SPA mode
Heating element	Copper tubular	Copper tubular
Type	Open outlet	Open outlet
Automatic flow switch	true	true
Heating material	Copper	Copper
Temperature setting	Variable 30-42 °C via Touch Control	Variable 30-42 °C via Touch Control
Temperature control	Electronic temperature control	Electronic temperature control
Temperature memory buttons	2	2
Anti-scalding protection	Double acting thermostat	Double acting thermostat
Shower accessories	5-in-1 head shower with slide bar	5-in-1 head shower with slide bar
Colour	silver	silver
IP rating	IP 25	IP 25
Cold water connection	1/2 inch	1/2 inch
Electrical fuse protection	ELCB	ELCB

<b>Rated output</b>	<b>3,500 W</b>	<b>4,500 W</b>
<b>Electrical connection</b>	<b>1/N/PE~220-240 V</b>	<b>1/N/PE~220-240 V</b>
<b>Rated voltage</b>	<b>220-240 V</b>	<b>220-240 V</b>
<b>Rated current</b>	<b>15.9 A</b>	<b>20.5 A</b>
<b>Display</b>	<b>Standard</b>	<b>Standard</b>
<b>Shutdown value</b>	<b>0.8 l/min</b>	<b>0.8 l/min</b>
<b>Starting flow rate</b>	<b>1.3 l/min</b>	<b>1.3 l/min</b>
<b>Depth</b>	<b>79 mm</b>	<b>79 mm</b>
<b>Height</b>	<b>326 mm</b>	<b>326 mm</b>
<b>Width</b>	<b>200 mm</b>	<b>200 mm</b>
<b>Weight</b>	<b>1.4 kg</b>	<b>1.4 kg</b>

## **Contact information**

**You have questions? We appreciate to help you:**

**Call 02-021-9300**

**Write an email to [th-info@stiebel-eltron.com](mailto:th-info@stiebel-eltron.com)**

## **Installation information**

**Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.**