

## WS 35 E-2 TITANIUM (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 208776

### The main features

Shower holder with adjustable height and tough tempered mirror

Polyamide anti-twist shower hose stays tangle-free

5-in-1 shower head with slide bar

Step-less temperature adjustment

ELSD protection against electricity leakage

Corrosion-resistant copper heating element and tank

Anti-scalding and overheating protection with double action thermostat

Heat and Flame Retardant PCB

Energy Efficient – EGAT Label No. 5 – 5 Star



WS 45 E-2 TITANIUM (STE)

Product-No.: 208777



| Type     | WS 35 E-2<br>TITANIUM (STE) | WS 45 E-2<br>TITANIUM (STE) |
|----------|-----------------------------|-----------------------------|
| Part no. | 208776                      | 208777                      |

## Technical data

|                            |                                      |                                      |
|----------------------------|--------------------------------------|--------------------------------------|
| Cold water connection      | 1/2 inch                             | 1/2 inch                             |
| Electrical fuse protection | ELSD                                 | ELSD                                 |
| Rated output               | 3,500 W                              | 4,500 W                              |
| Electrical connection      | 1/N/PE~220-240 V                     | 1/N/PE~220-240 V                     |
| Rated voltage              | 22 V                                 | 220 V                                |
| Rated current              | 15,9 A                               | 20,5 A                               |
| Heating element            | Copper tubular                       | Copper tubular                       |
| Type                       | Open outlet                          | Open outlet                          |
| Automatic flow switch      | true                                 | true                                 |
| Heating material           | Copper                               | Copper                               |
| Temperature setting        | Variable                             | Variable                             |
| Temperature control        | Output control                       | Output control                       |
| Anti-scalding protection   | Double acting<br>thermostat          | Double acting<br>thermostat          |
| Shower accessories         | 5-in-1 shower<br>head with slide bar | 5-in-1 shower<br>head with slide bar |
| Colour                     | grey                                 | grey                                 |

|                    |           |           |
|--------------------|-----------|-----------|
| IP rating          | IP25      | IP25      |
| Shutdown value     | 0.8 l/min | 0.8 l/min |
| Starting flow rate | 1.3 l/min | 1.3 l/min |
| Depth              | 79 mm     | 79 mm     |
| Height             | 326 mm    | 326 mm    |
| Width              | 200 mm    | 200 mm    |
| Weight             | 1.4 kg    | 1.4 kg    |

## **Contact information**

You have questions? We appreciate to help you:

Call 02-021-9300

Write an email to [th-info@stiebel-eltron.com](mailto:th-info@stiebel-eltron.com)

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.