

WSX 45 (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 207923

The main features

WSX 35 (STE)

Product-No.: 207922

Temperature adjustment via stepless power control

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

High-pressure larger copper tank with corrosion-free element

Safety indicator before every use ensures a worry-free shower experience

Shower set in refined titanium color with smooth-glide slider

5-in-1 shower head with slide bar for convenient height adjustment

Easy-wipe shower faceplate with ring nozzles

Anti-scalding and overheating protection with double action thermostat

Anti-twist polyamide shower hose prevents tangling

Flame-retardant electronic circuit board for extra safety

Type	WSX 35 (STE)	WSX 45 (STE)
Part no.	207922	207923

Technical data

Cold water connection	1/2 inch	1/2 inch
Electrical fuse protection	ELCB	ELCB
Rated output	3,500 W	4,500 W
Electrical connection	1/N/PE~220-230 V	1/N/PE~220-230 V
Rated voltage	220 V	220 V
Rated current	15,9 A	20,5 A
Heating element	Copper tubular	Copper tubular
Type	Open outlet	Open outlet
Automatic flow switch	true	true
Heating material	Copper	Copper
Temperature setting	Variable	Variable
Temperature control	Output control	Output control
Anti-scalding protection	Double acting thermostat	Double acting thermostat
Shower accessories	5-in-1 shower head with slide bar	5-in-1 shower head with slide bar
Colour	white	white
IP rating	IP25	IP25
Shutdown value	0.8 l/min	0.8 l/min
Starting flow rate	1.1 l/min	1.1 l/min
Depth	92 mm	92 mm

Height	345 mm	345 mm
Width	206 mm	206 mm
Weight	1.4 kg	1.4 kg

Contact information

You have questions? We appreciate to help you:

Call 02-021-9300

Write an email to th-info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.