

XG 38 EC (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 203188

The temperature control function of the X-TRA Tank makes showering extra safe, giving you peace of mind while other members of your household use the shower.

Featuring an extra slimline design with a depth of just 7.3 cm, as well as a striking colour contrast of pearl white and matte black, this model makes an eye-catching addition to every bathroom.

Furthermore, it comes with a power rating of 3800 or 4800 watts to heat your water faster.



The main features

Temperature adjustment via stepless power control

Complete set optimised for a single shower

X-TRA Tank – highly efficient composite polymer tank for reduced heat loss and electricity consumption

Corrosion-free copper heating element for longer service life

5-in-1 shower head with slide bar for convenient height adjustment

Extra slimline design with a depth of just 7.3 cm

Anti-scalding and overheating protection with double action thermostat

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

Protection class IP25 (splash-proof)



XG 45 EC (BLACK EDITION) (STE)

Product-No.: 200206



XG 48 EC (STE)

Product-No.: 203189



Type	XG 38 EC (STE)	XG 45 EC (BLACK EDITION) (STE)	XG 48 EC (STE)
Part no.	203188	200206	203189

Technical data

Cold water connection	1/2 inch	1/2 inch	
Electrical fuse protection	ELCB	ELCB	ELCB
Rated output	3,800 W	4,500 W	4,800 W
Rated current	17.3 A	20.5 A	21.9 A
Display	Standard	Standard	Standard
Heating element	COPPER TUBULAR	COPPER TUBULAR	COPPER TUBULAR
Type	Open outlet	Open outlet	Open outlet
Automatic flow switch	true	true	true
Heating material	X-TRA cylinder	X-TRA cylinder	X-TRA cylinder
Temperature setting	Variable	Variable	Variable
Temperature control	Output control	Output control	Output control
Anti-scalding protection	Double acting thermostat	Double acting thermostat	Double acting thermostat
Shower accessories	5-in-1 head shower with slide bar	5-in-1 head shower with slide bar	5-in-1 head shower with slide bar
Colour	white	black	white
IP rating	IP 25	IP 25	IP 25

Shutdown value	0.8 l/min	0.8 l/min	0.8 l/min
Starting flow rate	1.3 l/min	1.3 l/min	1.3 l/min
Depth	73 mm	73 mm	73 mm
Height	342 mm	342 mm	342 mm
Width	216 mm	216 mm	216 mm
Weight	1.8 kg	1.8 kg	1.8 kg

Contact information

You have questions? We appreciate to help you:

Call 02-021-9300

Write an email to th-info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.