

## XGL 38 EC (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 203190

No more sudden temperature fluctuations during your shower – even if another tap is in use at the same time – thanks to the precise electronic temperature control function.

Featuring an extra slimline design with a depth of just 7.3 cm, as well as a striking colour contrast of pearl white and matte black, this model makes an eye-catching addition to every bathroom.

Furthermore, it comes with a power rating of 3800 or 4800 watts to heat your water faster.



XGL 48 EC (STE)

Product-No.: 203191

### The main features

Maximum shower comfort with precise electronic output temperature control

---

Stepless temperature adjustment via rotary selector

---

LCD display shows the shower water temperature at a glance

---

Complete set optimised for a single shower

---

X-TRA Tank – highly efficient composite polymer tank for reduced heat loss and electricity consumption

---

Corrosion-free copper heating element for longer service life

---

5-in-1 shower head with slide bar for convenient height adjustment

---

Extra slimline design with a depth of just 7.3 cm

---

Anti-scalding and overheating protection with double action thermostat

---

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

---

Protection class IP25 (splash-proof)



Type	XGL 38 EC (STE)	XGL 48 EC (STE)
Part no.	203190	203191

## Technical data

Cold water connection	1/2 inch	1/2 inch
Electrical fuse protection	ELCB	ELCB
Rated output	3,800 W	4,800 W
Electrical connection	1/N/PE~220-240 V	1/N/PE~220-240 V
Rated voltage	220-240 V	220-240 V
Rated current	17.3 A	21.8 A
Display	Standard	Standard
Heating element	Copper tubular	Copper tubular
Type	Open outlet	Closed outlet
Automatic flow switch	true	true
Heating material	X-TRA cylinder	X-TRA cylinder
Temperature setting	Variable 30-42 °C	Variable 30-42 °C
Temperature control	Electronic temperature control	Electronic temperature control
Anti-scalding protection	Double acting thermostat	Double acting thermostat
Shower accessories	5-in-1 head shower with slide bar	5-in-1 head shower with slide bar

<b>Colour</b>	<b>white</b>	<b>white</b>
<b>IP rating</b>	<b>IP25</b>	<b>IP25</b>
<b>Shutdown value</b>	<b>0.8 l/min</b>	<b>0.8 l/min</b>
<b>Starting flow rate</b>	<b>1.3 l/min</b>	<b>1.3 l/min</b>
<b>Depth</b>	<b>73 mm</b>	<b>73 mm</b>
<b>Height</b>	<b>342 mm</b>	<b>342 mm</b>
<b>Width</b>	<b>216 mm</b>	<b>216 mm</b>
<b>Weight</b>	<b>1.5 kg</b>	<b>1.5 kg</b>

## **Contact information**

**You have questions? We appreciate to help you:**

**Call 02-021-9300**

**Write an email to [th-info@stiebel-eltron.com](mailto:th-info@stiebel-eltron.com)**

## **Installation information**

**Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.**