

EVS 100 (STE)

WALL MOUNTED CYLINDER

PRODUCT-NO.: 235871

Wall mounted storage water heaters from STIEBEL ELTRON are ideal for providing plentiful amounts of hot water in an instant, both in the bathroom and kitchen. We employ technology that is well known for its reliability and high level of safety. The special enamel coating and integral safety components we use enable us to guarantee a long service life for all of our storage water heaters. STIEBEL ELTRON has the right wall mounted storage water heater to suit every conceivable installation scenario, for a fast and flexible supply of hot water to one or more draw-off points.

The main features

User friendly temperature adjustment with control selector on the front

Sufficient hot water for multiple draw-off points

Thermometer with actual temperature indicator

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)



EVS 15 (STE)

Product-No.: 235867



EVS 30 (STE)

Product-No.: 235868



EVS 50 (STE)

Product-No.: 235869



EVS 80 (STE)

Product-No.: 235870



EVS 150 (STE)

Product-No.: 235872



Type	EVS 15 (STE)	EVS 30 (STE)	EVS 50 (STE)
Part no.	235867	235868	235869

Technical data

Height	543 mm	615 mm	745 mm
Width	305 mm	365 mm	390 mm
Diameter	305 mm	365 mm	390 mm
Weight	10.8 kg	12.6 kg	17.1 kg
Installation type	Wall mounting, horizontal	Wall mounting, horizontal	Wall mounting, horizontal
Safety valve	Pressure safety valve	Pressure safety valve	Pressure safety valve
IP rating	IPX4	IPX4	IPX4
Cable length	1.3 m	1.3 m	1.3 m
Cylinder material	Steel, enamel	Steel, enamel	Steel, enamel
Heating element material	Incoloy	Incoloy	Incoloy
Thermal insulation material	PU foam	PU foam	PU foam
Temperature range	up to 75 °C	up to 75 °C	up to 75 °C
Nominal capacity	15 l	30 l	50 l
Max. water inlet pressure	0.7 MPa	0.7 MPa	0.7 MPa
Electrical connection	1/N/PE~220-240 V	1/N/PE~220-240 V	1/N/PE~220-240 V
Rated current	9.5 A	9.5 A	9.5 A
Rated output	1,500 W	2,000 W	2,000 W



Type	EVS 80 (STE)	EVS 100 (STE)	EVS 150 (STE)
Part no.	235870	235871	235872

Technical data

Height	740 mm	880 mm	1230 mm
Width	460 mm	460 mm	460 mm
Diameter	460 mm	460 mm	460 mm
Weight	23.3 kg	27.6 kg	34.9 kg
Installation type	Wall mounting, horizontal	Wall mounting, horizontal	Wall mounting, horizontal
Safety valve	Pressure safety valve	Pressure safety valve	Pressure safety valve
IP rating	IPX4	IPX4	IPX4
Cable length	1.3 m	1.3 m	1.3 m
Cylinder material	Steel, enamel	Steel, enamel	Steel, enamel
Heating element material	Incoloy	Incoloy	Incoloy
Thermal insulation material	PU foam	PU foam	PU foam
Temperature range	up to 75 °C	up to 75 °C	up to 75 °C
Nominal capacity	1.3 l	100 l	150 l
Max. water inlet pressure	0.7 MPa	0.7 MPa	0.7 MPa
Electrical connection	1/N/PE~220-240 V	1/N/PE~220-240 V	1/N/PE~220-240 V
Rated current	9.5 A	9.5 A	9.5 A
Rated output	2,000 W	2,000 W	2,000 W

Contact information

You have questions? We appreciate to help you:

Call 02-021-9300

Write an email to th-info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.