

## FOUNTAIN 7S (COPPER GOLD) (STE)

DOMESTIC USE PRODUCT-NO.: 238762

The elegant design for kitchen countertop installation enhances any kitchen interior and features:

- 7-in-1 ultrafiltration system for 100 % removal of bacteria with no water wastage or storage tank
- A smart battery and filter lifetime indicator
- Certified drinking water safety to NSF Standard 42 & 53
- 360° flexible dispenser pipe for use over a wider area
- No electricity needed for operation

The main features

7 stages in 1 cartridge for easier filter replacement

Certified drinking water safety to NSF Standard 42 & 53

No electricity needed for operation

360° flexible dispenser pipe for use over a wider radius

One-way dispenser nozzle to prevent contamination from outside

Durable ceramic ON/OFF-valve at the front for more convenient operation

Indicator for filter lifetime - 4320 litres or 12 months, whichever comes first





FOUNTAIN 7S (SILVER) (STE)

Product-No.: 201588



FOUNTAIN 7S ANTHRACITE (STE)

Product-No.: 204000









Туре			
Part no.			

FOUNTAIN			
7S (COPPER			
GOLD) (STE)			

FOUNTAIN 7S (SILVER) (STE) FOUNTAIN 7S ANTHRACITE (STE)

## Technical data

Height	370 mm	345 mm	345 mm
Width	220 mm	160 mm	160 mm
Depth	185 mm	170 mm	170 mm
Weight	4 kg	4 kg	4 kg
Filtration stages	7 Stage	7 Stage	7 Stage
Filter stage 1	Sediment - 5 #m	Sediment - 5 #m	Sediment - 5 #m
Filter stage 2	Activated carbon block - 1 #m	Activated carbon block - 1 #m	Activated carbon block - 1 #m
Filter stage 3	Far infrared radiation ceramic balls	Far infrared radiation ceramic balls	Far infrared radiation ceramic balls
Filter stage 4	Negative ion ceramic balls	Negative ion ceramic balls	Negative ion ceramic balls
Filter stage 5	Granulated activated carbon with silver impregnation	Granulated activated carbon with silver impregnation	Granulated activated carbon with silver impregnation
Filter stage 6	Ultra filtration (hollow fibre) - 0.1-0.01 #m	Ultra filtration (hollow fibre) - 0.1-0.01 #m	Ultra filtration (hollow fibre) - 0.1-0.01 #m
Filter stage 7	Silverlite stone	Silverlite stone	Silverlite stone



Nominal flow rate	2.7 l/min	2.7 l/min	2.7 I/min
Max. operating pressure	4 bar	4 bar	4 bar
Temperature range	4 - 35 °C	4 - 35 °C	4 - 35 °C
Min. operating pressure	1 bar	1 bar	1 bar
Max. flow rate	4 I/min	4 I/min	4 I/min
Maximum water pressure	4 bar	4 bar	4 bar
Draw-off option	Flexible hose	Flexible hose	Flexible hose
Colour	copper gold	silver grey	anthracite
Installation type	Oversink	Oversink	Oversink



## **Contact information**

You have questions? We appreciate to help you: Call 02-021-9300 Write an email to th-info@stiebel-eltron.com

## Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.